



## MEDIUM PRESSURE STOPPERS Small Diameter



For pressure testing and temporary sealing of gas, water, oil and sewerage pipes made of steel, cast iron, clay, plastic and concrete.

For maximum allowable back pressures for each size of plug, please see Datasheet below.

Sizes 14mm up to 75mm inclusive have a single seal, sizes 80mm to 500mm are supplied with double seal.

Triple seals are available as an option. Prices on request. Compression plates are made of cast aluminium. Cat No 300AE has 3 clamping screws which makes the plug especially suitable for pipes with grooving or slight ovality.

**Please note that plugs must be suitably braced when applying any back pressure, in order to prevent the risk of accident.**

Dia mm	Pipe ID		Insert Into Pipe	Water Way	Maximum Pressure	Weight of Plug	Length of Plug
	Min	Max					
14	14	16	50mm	3mm	30.0bar	0.32kg	200mm
16	16	20	50mm	4mm	30.0bar	0.32kg	240mm
20	20	25	50mm	4mm	30.0bar	0.34kg	240mm
25	23	29	50mm	4mm	30.0bar	0.36kg	240mm
30	28	34	60mm	8mm	25.0bar	0.52kg	280mm
35	33	39	60mm	8mm	20.0bar	0.55kg	280mm
40	38	45	60mm	8mm	20.0bar	0.60kg	280mm
50	48	55	60mm	8mm	20.0bar	0.69kg	280mm

The company follow a policy of continuous product development and as such reserves the right to make alterations to equipment and techniques without prior notice.

### PIPE EQUIPMENT SPECIALISTS LTD

66 DUKESWAY, TEESIDE INDUSTRIAL ESTATE, THORNABY, STOCKTON-ON-TEES, TS17 9LT, ENGLAND

**TEL: +44 (0) 1642 769789 FAX: +44 (0) 1642 769456**

**www.pipe-equipment.co.uk Email: info@pipe-equipment.co.uk**



Certificate Number: 1253  
WP/TIS/MPSSD/0415